



PEAK -20 °F De-Icer Windshield Wash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 01/01/2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : PEAK -20 °F De-Icer Windshield Wash
Product code : PWN0G3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Windshield washer fluid

1.3. Details of the supplier of the safety data sheet

Old World Industries, LLC
3100 Sanders Road
Northbrook, IL 60062 - USA
T (847) 559-2000
www.oldworldind.com

1.4. Emergency telephone number

Emergency number : 800 424 9300 (United States); 00 1 703 527 3887 (International)
Chemtrec

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

| | | |
|--|------|--|
| Flammable liquids, Category 3 | H226 | Flammable liquid and vapor |
| Acute toxicity (oral), Category 4 | H302 | Harmful if swallowed. |
| Acute toxicity (dermal), Category 3 | H311 | Toxic in contact with skin. |
| Acute toxicity (inhalation:dust,mist), Category 4 | H332 | Harmful if inhaled. |
| Specific target organ toxicity — single exposure, Category 1 | H370 | Causes damage to organs (May cause blindness if swallowed) |

Full text of H statements : see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Flammable liquid and vapor
Harmful if swallowed or if inhaled
Toxic in contact with skin.
Causes damage to organs (May cause blindness if swallowed)

Precautionary statements (GHS-US) :

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. heat, hot surfaces, open flames, sparks
Keep container tightly closed.
Ground/Bond container and receiving equipment
Use explosion-proof electrical, lighting, ventilating equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe mist, spray, vapors
Wash affected areas thoroughly after handling.

PEAK -20 °F De-Icer Windshield Wash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS-US) *continued* :

- Do not eat, drink or smoke when using this product.
- Use only outdoors or in a well-ventilated area.
- Wear personal protective equipment as required.
- If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
- If inhaled: Remove person to fresh air and keep comfortable for breathing
- If exposed: Call a poison center/doctor
- If swallowed: Immediately call doctor/physician or poison center. Rinse Mouth
- Call doctor/physician or poison center if you feel unwell
- Take off immediately all contaminated clothing and wash it before reuse.
- In case of fire: Use Carbon dioxide, Dry powder, foam, sand to extinguish.
- Store in a well-ventilated place. Keep cool.
- Store locked up.
- Dispose of contents/container to appropriate waste disposal facility, in accordance with local/regional/national/international regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % by wt | GHS-US classification |
|----------|---------------------|---------|--|
| water | (CAS-No.) 7732-18-5 | >= 67 | Not classified |
| methanol | (CAS-No.) 67-56-1 | <= 33 | Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370 |

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek immediate medical advice. Allow the victim to rest. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

First-aid measures after skin contact : Take off immediately all contaminated clothing. Rinse immediately with plenty of water (for at least 15 minutes). If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse immediately with plenty of water for 15 minutes, lifting lower and upper lids. Take victim to an ophthalmologist if irritation persists.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Rinse mouth. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : High concentrations may cause central nervous system characterized by severe headaches, dizziness, nausea and confusion. May cause irritation of the nose and throat.

Symptoms/effects after skin contact : Prolonged exposure to skin may cause skin irritation experienced as burning, dryness, cracking and redness.

Symptoms/effects after eye contact : May cause severe irritation.

Symptoms/effects after ingestion : May cause nausea, abdominal pain, headache, shortness of breath, visual impairment and blindness. Severe poisoning can lead to coma and death.

Chronic symptoms : ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin, Dry skin, Skin rash/inflammation, Headache, Feeling of weakness, Disturbed tactile sensibility, Visual disturbances, Sleeplessness, Gastrointestinal complaints, Cardiac and blood circulation effects.

PEAK -20 °F De-Icer Windshield Wash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Indication of any immediate medical attention and special treatment needed

Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. This product contains/consists of methanol which can cause intoxication and depression of the central nervous system.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : ABC powder. Foam. Dry powder. Carbon dioxide. Sand.
Unsuitable extinguishing media : Do not use a heavy water stream. May spread fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor. Vapors are heavier than air and may travel along the ground or may be moved by ventilation.
Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Do not breathe mist, spray, vapors. In case of inadequate ventilation wear respiratory protection. Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel. Keep upwind. Mark the danger area.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain released product, pump into suitable containers. Dam up the liquid spill. Plug the leak, cut off the supply. Try to reduce evaporation. Take account of toxic/corrosive precipitation water. Dilute combustible/toxic gases/vapors with water spray.
Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : In use, may form flammable vapor-air mixture.
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.
Hygiene measures : Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Use explosion-proof ventilating, lighting, electrical equipment. Ground/bond container and receiving equipment. Proper grounding procedures to avoid static electricity should be followed.
Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources, hot surfaces, open flames, sparks. Keep container closed when not in use. Do not store near food, foodstuffs, drugs or potable water supplies. Do not cut, drill, weld, use a blowtorch on, etc. containers even when empty.
Incompatible products : Keep away from strong acids, strong bases and oxidizing agents.
Incompatible materials : Sources of ignition.

PEAK -20 °F De-Icer Windshield Wash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| methanol (67-56-1) | | |
|--------------------|-------------------------------------|--------------------------------------|
| ACGIH | Local name | Methanol |
| ACGIH | ACGIH TWA (ppm) | 200 ppm (Skin) |
| ACGIH | ACGIH STEL (ppm) | 250 ppm (Skin) |
| ACGIH | Remark (ACGIH) | Headache; eye dam; dizziness; nausea |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 260 mg/m ³ (Skin) |
| OSHA | OSHA PEL (TWA) (ppm) | 200 ppm (Skin) |

| water (7732-18-5) | | |
|-------------------|--|--|
| Not applicable | | |

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Gloves. Safety glasses.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Wear appropriate mask



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|--------------------------------|
| Physical state | : Liquid |
| Color | : Blue |
| Odor | : alcohol |
| Odor threshold | : No data available |
| Relative evaporation rate (butylacetate=1) | : Greater than n-butyl acetate |
| Freezing point | : -28.9 °C (-20 °F) |
| Boiling point | : 81.7 °C (179 °F) |
| Flash point | : 33.3 °C (92 °F) |
| Auto-ignition temperature | : No data available |

PEAK -20 °F De-Icer Windshield Wash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---------------------------------|---------------------|
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapor pressure | : 43 mm Hg @ 20 °C |
| Relative vapor density at 20 °C | : Heavier than air |
| Specific Gravity | : 0.96 @ 20 °C |
| Solubility | : Water: Complete |
| Log Pow | : No data available |
| Log Kow | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive limits | : 6 - 36 vol % |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |

9.2. Other information

VOC content : < 33 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Keep away from strong acids, strong bases and oxidizing agents.

10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| methanol (67-56-1) | |
|----------------------------|--|
| LD50 oral rat | 1187 - 2769 mg/kg bodyweight (BASF test, Rat, Male / female, Weight of evidence, Aqueous solution, Oral, 7 day(s)) |
| LD50 dermal rabbit | 17100 mg/kg (Rabbit, Inconclusive, insufficient data, Dermal) |
| LC50 inhalation rat (mg/l) | 128.2 mg/l/4h (BASF test, 4 h, Rat, Male/female, Weight of evidence) |
| ATE US (oral) | 100 mg/kg bodyweight |
| ATE US (dermal) | 300 mg/kg bodyweight |
| ATE US (gases) | 700 ppmv/4h |
| ATE US (vapors) | 3 mg/l/4h |
| ATE US (dust,mist) | 0.5 mg/l/4h |

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Causes damage to organs (May cause blindness if swallowed) .

STOT-repeated exposure : Not classified

PEAK -20 °F De-Icer Windshield Wash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|-------------------------------------|--|
| Aspiration hazard | : Not classified |
| Symptoms/effects after inhalation | : High concentrations may cause central nervous system characterized by severe headaches, dizziness, nausea and confusion. May cause irritation of the nose and throat. |
| Symptoms/effects after skin contact | : Prolonged exposure to skin may cause skin irritation experienced as burning, dryness, cracking and redness. |
| Symptoms/effects after eye contact | : May cause severe irritation. |
| Symptoms/effects after ingestion | : May cause nausea, abdominal pain, headache, shortness of breath, visual impairment and blindness. Severe poisoning can lead to coma and death. |
| Chronic symptoms | : ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin, Dry skin, Skin rash/inflammation, Headache, Feeling of weakness, Disturbed tactile sensibility, Visual disturbances, Sleeplessness, Gastrointestinal complaints, Cardiac and blood circulation effects. |

SECTION 12: Ecological information

12.1. Toxicity

| methanol (67-56-1) | |
|--------------------|--|
| LC50 fish 1 | 15,400.00 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal) |
| EC50 Daphnia 1 | 18,260.00 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Locomotor effect) |
| ErC50 (algae) | 22,000.00 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value) |

12.2. Persistence and degradability

| methanol (67-56-1) | |
|---------------------------------|--|
| Persistence and degradability | Readily biodegradable in the soil. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 0.6 - 1.12 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 1.42 g O ₂ /g substance |
| ThOD | 1.50 g O ₂ /g substance |

12.3. Bioaccumulative potential

| methanol (67-56-1) | |
|---------------------------|---|
| BCF fish 1 | 1 - 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value) |
| Log Pow | -0.77 (Experimental value) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). |

12.4. Mobility in soil

| methanol (67-56-1) | |
|--------------------|---|
| Surface tension | 0.02 N/m (20 °C) |
| Log Koc | 0.09 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |
| Ecology - soil | Highly mobile in soil. |

12.5. Other adverse effects

| | |
|---------------------------|--------------------------------------|
| Effect on the ozone layer | : No known effect on the ozone layer |
| Other information | : Avoid release to the environment. |

SECTION 13: Disposal considerations

13.1. Waste treatment methods

| | |
|--|---|
| Product/Packaging disposal recommendations | : Dispose of contents/container to appropriate waste disposal facility, in accordance with local/regional/national/international regulations. |
| Ecology - waste materials | : Avoid release to the environment. |

SECTION 14: Transport information

PEAK -20 °F De-Icer Windshield Wash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Department of Transportation (DOT)

In accordance with DOT

Non-Bulk:

In inner packaging no more than 5.0 L (1.3 Gallons): Proper Shipping Name: Limited Quantity of Class III Per 49 CFR Part 173.150 (PG III, inner packaging no more than 5.0L)

Bulk (in quantities larger than 5.0L [1.3 gallons] in a single container)

| | |
|--------------------------------|---|
| Transport document description | : UN1993 Flammable liquids, n.o.s., 3, III |
| UN-No.(DOT) | : UN1993 |
| Proper Shipping Name (DOT) | : Flammable liquids, n.o.s. |
| Class (DOT) | : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120 |
| Packing group (DOT) | : III - Minor Danger |
| Hazard labels (DOT) | : 3 - Flammable liquid |



| | |
|--|---|
| DOT Packaging Non Bulk (49 CFR 173.xxx) | : 203 |
| DOT Packaging Bulk (49 CFR 173.xxx) | : 242 |
| DOT Symbols | : G - Identifies PSN requiring a technical name |
| DOT Packaging Exceptions (49 CFR 173.xxx) | : 150 |
| DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) | : 60 L |
| DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) | : 220 L |
| DOT Vessel Stowage Location | : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel. |
| Emergency Response Guide (ERG) Number | : 128 |
| Other information | : No supplementary information available. |

Transportation of Dangerous Goods

Refer to current TDG Canada for further Canadian regulations

Transport by sea

In accordance with IMDG / IMO

| | |
|---------------------------------------|---|
| Transport document description (IMDG) | : UN 1992 Flammable Liquid, Toxic, n.o.s. (methanol) , 3, III |
| UN-No. (IMDG) | : 1992 |
| Proper Shipping Name (IMDG) | : Flammable Liquid, Toxic, n.o.s. (methanol) |
| Class (IMDG) | : 3 - Flammable liquids |
| Packing group (IMDG) | : III - substances presenting low danger |

Air transport

In accordance with IATA / ICAO

| | |
|---------------------------------------|--|
| Transport document description (IATA) | : UN 1992 Flammable Liquid, Toxic, n.o.s. (methanol), 3 (6.1), III |
| UN-No. (IATA) | : 1992 |
| Proper Shipping Name (IATA) | : Flammable Liquid, Toxic, n.o.s. (methanol) |
| Class (IATA) | : 3 - Flammable Liquids |
| Packing group (IATA) | : III - Minor Danger |
| Subsidiary risks (IATA) | : 6.1 - Toxic substances |

PEAK -20 °F De-Icer Windshield Wash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

| PEAK -20 °F De-Icer Windshield Wash | |
|--|---|
| EPA TSCA Regulatory Flag | Toxic Substances Control Act (TSCA): The intentional ingredients of this product are listed |
| SARA Section 302 Threshold Planning Quantity (TPQ) | None |
| SARA Section 311/312 Hazard Classes | Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard |
| SARA Section 313 - Emission Reporting | 33 % (Methanol CAS # 67-56-1) |

methanol (67-56-1)

CERCLA RQ 5000 lb(s) (2270 kg)

water (7732-18-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

PEAK -20 °F De-Icer Windshield Wash

WHMIS Classification This SDS has been prepared according to the criteria of the Hazardous Products Regulations (HPR) (WHMIS 2015) and the SDS contains all of the information required by the HPR. Applicable GHS information is listed in section 2.2 of this SDS.

15.3. US State regulations

⚠ WARNING: This product can expose you to methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

methanol (67-56-1)

| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) | Maximum allowable dose level (MADL) |
|---|---|---|---|----------------------------------|--|
| No | Yes | No | No | | 47000 µg/day (inhalation); 23,000 µg/day (oral) |

methanol (67-56-1)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date : 01/01/2020

Full text of H-statements:


| | |
|------|-----------------------------------|
| H225 | Highly flammable liquid and vapor |
| H226 | Flammable liquid and vapor |
| H301 | Toxic if swallowed. |
| H302 | Harmful if swallowed. |
| H311 | Toxic in contact with skin. |
| H331 | Toxic if inhaled. |
| H332 | Harmful if inhaled. |
| H370 | Causes damage to organs |

PEAK -20 °F De-Icer Windshield Wash

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|--------------------|---|
| NFPA health hazard | : 1 - Materials that, under emergency conditions, can cause significant irritation. |
| NFPA fire hazard | : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions. |
| NFPA reactivity | : 0 - Material that in themselves are normally stable, even under fire conditions. |



SDS GHS US (GHS HazCom 2012) OWI

Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.